

# Sapphire<sup>®</sup> Plus Lesion Detection

Test the light output using the Sapphire LSU internal light meter before every examination. With the LSU in the Optional bL mode for Sapphire Supreme or the Scope mode for Sapphire Plus to activate the lamp. Place the front of the scope directly on top of the light meter window so that the window is in the center of the illumination spot. View the positioning over the meter window through the scope while doing this then check the reading on the four digit display without moving the scope.

If the light output is 00 75 or higher, record the value, date, and initial the log. Make additional copies of this calibration log as needed.

DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE
Value	Value	Value	Value	Value	Value	Value	Value	Value	Value	Value	Value	Value
Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial

DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE
Value	Value	Value	Value	Value	Value	Value	Value	Value	Value	Value	Value	Value
Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial

DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE
Value	Value	Value	Value	Value	Value	Value	Value	Value	Value	Value	Value	Value
Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial

DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE	DATE
Value	Value	Value	Value	Value	Value	Value	Value	Value	Value	Value	Value	Value
Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial	Initial

